

ORDER FORM - CONTEMPORARY (FLAT) CASEMENT WINDOW

Page of

Invoice Name & Address:	Customer Ref:	Secured By Design <input type="checkbox"/> Doc Q compliant <input type="checkbox"/>
	Date Required:	Part L Compliant Products: <input type="checkbox"/>
	Previous Quote No:	BFRG Energy Rated Products: B <input type="checkbox"/>
	Works Order No:	Authorised Retailer - Energy Rated Product
Telephone:	Date Received:	AR No: <input type="text"/> AR <input type="checkbox"/> B <input type="checkbox"/>

FRAME CONSTRUCTION: Internally (dummy sashes will be required) Outer: AW605 53x58mm ☐ AW604 43x58mm ☐ Sash: AW685 45mm Flat T Sash Transom / Mullion: AW632 57mm

FRAME FINISH: White (RAL9910 gloss)* ☐ RAL: on White (RAL9910 gloss) ☐ RAL: on RAL: ☐ *RAL9910 Gloss is our standard White






GLAZING BEAD: Square **GASKET TYPE:** Black ☐ Anthracite Grey ☐

HANDLE TYPE & COLOUR: STANDARD: ☐ Colour: CONTEMPORARY: ☐ Handle Type: Colour: Please see spec sheets on our website for handles styles & colours

Item	O/All Size		Qty	Design No.	Mullion Break	Transom Drop	Glazing		Glass Description	Spacer Bar Colour*	Add on/ Coupler	Cill Type	Cill Length**	Hinge Type		Hinge Guard	Part F Slot Vent in 73mm Head
	Width	Height					U/G	D/G						Egr	Rest		
1																	
2																	
3																	
4																	
5																	

View all Windows from **OUTSIDE** – including Tilt & Turn Windows

**Std cill length = frame width +100mm

1	2	3	4	5
 <p>Floating Mullion Req <input type="checkbox"/></p> <p>Part F <input type="checkbox"/> Compliant Slot Vents</p>	 <p>Floating Mullion Req <input type="checkbox"/></p> <p>Part F <input type="checkbox"/> Compliant Slot Vents</p>	 <p>Floating Mullion Req <input type="checkbox"/></p> <p>Part F <input type="checkbox"/> Compliant Slot Vents</p>	 <p>Floating Mullion Req <input type="checkbox"/></p> <p>Part F <input type="checkbox"/> Compliant Slot Vents</p>	 <p>Floating Mullion Req <input type="checkbox"/></p> <p>Part F <input type="checkbox"/> Compliant Slot Vents</p>

Special Requirements:

Ordering Notes:

Glazing: 28mm glazing as standard ***Spacer Bar:** Black warm edge spacer bar as standard.
Min/Max Heights: For size limitations see data sheets in the Technical section of our website
Transom/Mullion: AW632 will be used on these windows
Cill Height: 25mm ****Cill sizes available:** 95 / 150 / 190mm
Locks: Shootbolt locking as standard
Frame Add On: 20mm only **Coupler:** 15mm & 26mm available

Important:

Before ordering please ensure that you are familiar with our products and specifications as we will not accept responsibility for want of knowledge in the event that items manufactured do not meet with your requirements. This order cannot be accepted unless signed below.

Signed :