A	lu-	tec
Windo	ows &	Doors

Please do not write in the white space around the form. This does not replicate when faxing. Use special requirements box for any further information.

		Λlı	1	to		OR	DE	RF	ORM	l - AL	UMINIL	JM	CAS	SEME	ĒΝ	IT WIND	OOW					Page	of							
Alu-tec ORDE Invoice Name &						me & Address:					Сι	ustome	er Ref:				Se	Secured By Design Doc				mpliant 🔲								
													ate Re	quired:				Pa	Part L Compliant Products:											
-5 Fletchers Square, Temple Farm Ind Estate,											Pr	Previous Quote No:						BFRC Energy Rated Products: A B B												
utton Road, Southend-on-Sea, ssex SS2 5RN												Inrks C	order No					Authorised Retailer - Energy Rated Product												
el: (01702) 899440 Fax: (01702) 307180 Telephone:										Works Order No:  Date Received:							No: AR	а П В												
FRAME CONSTRUCTION: Externally Glazed System Internally Glazed System - dummy sashes will be required I																														
FRAME FINISH: White (RAL9910 gloss)* RAL:									on White (RAL9910 gloss)				RAL: on RAL:						*RAL9910 Gloss is our standard White											
GLAZING THICKNESS & BEAD TYPE: 28mm 32mm Chamfered Square Black gasket Anthracite Grey gasket																														
	ANDLE TYPE STANDARD: Colour:  CONTEMPORARY: Handle Type:  CONTEMPORARY: Handle Type:  COLOUR:																													
		CONTEN	/IPOR/	ARY:	Handle <sup>-</sup>	Type:	1	Colo							<b>5</b> 11				<u> </u>	1										
	O/All S			Design		Transom		Glass		Spacer Bar		uter			Transom/	Add on/	Cill	Cill		Туре	Hinge	Part F Slot Vent in 73mm								
em	Width	Height	Qty	No.	Break	Drop	U/G	D/G	Description		Colour	Frame*		Sash*	ŕ	Mullion*	Coupler	Туре	Length**	Egr	Rest	Guard	Head							
1																	$\times$													
2																														
_																														
3																														
4																														
5																	$\times$													
View all Windows from <b>OUTSIDE</b> – including Tilt & Turn Windows  **Std cill length = frame width +100mm														0mm																
1					2					3				- 4	4				5											
Floating Mullion Reqd					Floatin Mullion Reqd				on <u></u>			Floating Mullion Reqd					Floating Mullion Reqd	lion				Floating Mullion Reqd								
Part F Compliant Slot Vents					Part F Compliant Slot Vents					Part F Compliant Slot Vents					Part F Complia					Part F Compliant Slot Vents										
noci	al Poquiro	monte:						Ord	dering N	otes:	tandard / 20	ICI	Lavailet	1-				Impo	rtant:	Ordering Notes:    Important:										

Glazing: 28mm glazing as standard / 32mm IGU available
\*Spacer Bar: Black warm edge spacer bar as standard.
Min/Max Heights: For size limitations see data sheets in the Technical section of our website.

Gasket Colour: Black or Anthracite Grey

Cill Height: 25mm \*\*Cill sizes available: 95 / 150 / 190mm Locks: Shootbolt locking as standard

Frame Add On: 20mm. 40mm available for 70mm system only. Coupler: 15mm & 26mm available

Before ordering please ensure that you are familiar with our products and specifications as we will not accept responsibility for want of knowledge in the event that items manufactured do not meet with your requirements. This order cannot be accepted unless signed below.

Signed: