AI	<b>u</b> -1	tec
Windo	ws & D	oors

Please do not write in the white space around the form. This does not replicate when faxing. Use special requirements box for any further information.

		<b>.</b> I	<b>1</b> ~		ORDER FORM - OVOLO CASEMENT WINDOW													of	
		\lu-	TE	;C	Invoice N	lame & Add	dress:			Customer R		Secured By Design Doc Q compliant							
	Wi	ndows & [	5						Date Require		Part L Compliant Products:								
		e, Temple Farn	state,						Previous Qu										
Sutton Road, Southend-on-Sea, Essex SS2 5RN Tel: (01702) 899440 Fax: (01702) 307180					Telephor	ne:				Works Orde Date Receiv									
FRAN	IE CONSTRU	CTION - Exter	rnally G	lazed Sy	stem Out	er: AW602	53x70m	m Standa	ard Sash: AW	/613 67mm Ext g	lazed <b>Tran</b>	som / Mulli	ion: AW632	57mm					
FRAME FINISH: White (RAL9910 gloss)* RAL: on White (RAL9910 gloss)									AL9910 gloss)	RAL:	on RAL: *RAL9910 Gloss is our standard White								
GLAZ	ING BEAD:	Bevel <b>G</b>	GASKE <sup>*</sup>	T TYPE:	Black	Anthracite	Grey												
		STANDARD:	Col	our:									Please s	ee spec sheets	on our we	ebsite for	handles sty	les & colour:	
& CC	DLOUR:	CONTEMPOR	ARY:	Handl	е Туре:				Colo	ur:									
	O/All Siz	ize		Design	Mullion	Transom	Glaz	zing			0	. Add on/	Cill	Cill	Hinge Type			Slot Venin 73mm	
Item	Width	Height	Qty	No.	Break	Drop	U/G	D/G	Glass De	scription	Spacer Bar Colour*	Coupler	Туре	Length**	Egr	Rest	Hinge Guard	Head	
1																			

4

	O/All Size				Mullion	Transom	Glazing			Spacer Bar	Add on/	Cill	Cill	Hinge Type		Llings	Slot Vent in 73mm Head
Item	Width	Height	Qty	Design No.	Break	Drop	U/G	D/G	Glass Description		Coupler		Length**	Egr	Rest	Hinge Guard	Head
1																	
2																	
3											$\times$						
4											$\times$						
5																	
View all Windows from <b>OUTSIDE</b> – including Tilt & Turn Windows												**Std cil	**Std cill length = frame width +100mr				

## Special Requirements:

Floating

Mullion\_

Reqd Part F

Compliant

Slot Vents

2

## **Ordering Notes:**

Floating

Mullion

Regd

Part F

Compliant

Slot Vents

3

Glazing: 28mm glazing as standard \*Spacer Bar: Black warm edge spacer bar as standard. Min/Max Heights: For size limitations see data sheets in the Technical section of our website. Transom/Mullion: AW632 will be used on these windows

Floating

Mullion

Regd

Part F

Compliant

Slot Vents

Cill Height: 25mm \*\*Cill sizes available: 95 / 150 / 190mm

Locks: Shootbolt locking as standard

Frame Add On: 20mm. 40mm available for 70mm system only. Coupler: 15mm & 26mm available

## Important:

Floating

Mullion

Regd

Part F

Compliant

Slot Vents

5

Before ordering please ensure that you are familiar with our products and specifications as we will not accept responsibility for want of knowledge in the event that items manufactured do not meet with your requirements. This order cannot be accepted unless signed below.

Signed:

0325ALOV-Issue 5 01-24

Floating

Mullion

Regd

Part F

Compliant

Slot Vents