Alu	ı-tec
Windows	& Doors

Please do not write in the white space around the form. This does not replicate when faxing. Use special requirements box for any further information.

		N I	. .		0	RDER	FOR	M	ALUMINIUN	/ FLUSH	WINDO	W				Г	Page	of
		الا-	TE	Invoice Name & Address:						Customer R					L			
Windows & Doors							Date Require	ed:										
1-5 Fle	etchers Squar	re, Temple Farr	m Ind F	state						Previous Qu	ote No:							
Sutton	Road, South	end-on-Sea,		o tato,						Works Orde								
Tel: (0	1702) 89944	0 Fax: (01702)	307180	0	Telepho	ne:				Date Receiv		Part L Compliant Products:						
		JCTION: Intern 70mm U44							ny sashes) AW685 45mm Fla	t Line T Sash	AW686 45m	m Stepped	Edge Sasl	n Tran	s/Mull: U	J44043		
FRAN	ME FINISH:	White (RAL99	910 glos	ss)*	RAL:		on	White ((RAL9910 gloss)	RAL:		on RAL:			*RAL99	10 Gloss	is our star	idard White
GLAZ	ING BEAD:	Square (stan	dard)	GAS	KET TYPE	: Black												
HAN	DLE TYPE	STANDARD:	Со	lour:									Please	see spec sheets	on our we	ebsite for	handles sty	les & colours
& CC	DLOUR:	CONTEMPOR	ARY:	Handl	е Туре:				Colou	r:								
	O/All Si	ze		Design	Mullion	Transom	Glaz	zing			Spacer Bar	Add on/	Cill	Cill	Hinge Type		l line and	Slot Vent in 73mm
Item	Width	Height	Qty	No.	Break	Drop	U/G	D/G	Glass Des	cription	Colour*	Coupler	Туре	Length**	Egr	Rest	Hinge Guard	Head
1														**Std c				
2														ill length				
3														n = fram				
4														e width -				
5														100 mm				
		!	•					V	iew all Windows fr	om OUTSIDE		V Y						1
1				2				3			4							
								lг		\neg				l				

	View all Windows from OUTSIDE		
2	3	4	5

Part F Compliant Slot Vents		Part F Compliant Slot Vents	1 1	Part F Compliant		Part F Compliant		Part F Compliant
Slot Vents	L	Slot Vents		Slot Vents	L	Slot Vents		Slot Vents

Special Requirements:	
_	

Ordering Notes:

Glazing: 28mm glazing as standard *Spacer Bar: Black warm edge spacer bar as standard. Min/Max Heights: For size limitations, please refer to the data sheets in the Technical

Section of our website

Cill Height: 25mm **Cill sizes available: 95 / 150 / 190mm

Locks: Shootbolt locking as standard

Frame Add On: 20mm and 40mm only Coupler: 15mm & 26mm available

Important:

Before ordering please ensure that you are familiar with our products and specifications as we will not accept responsibility for want of knowledge in the event that items manufactured do not meet with your requirements. This order cannot be accepted unless signed below.

Signed: